

CITY OF LAKE ELMO
COUNTY OF WASHINGTON
STATE OF MINNESOTA

30
ORDINANCE NO. 08-229

**AN ORDINANCE AMENDING THE LAKE ELMO CITY ZONING CODE OF
ORDINANCES BY AMENDING THE HEIGHT STANDARDS FOR ACCESSORY
STRUCTURES AND REDEFINING HOW BUILDING HEIGHT IS DETERMINED.**

SECTION 1. The City Council of the City of Lake Elmo hereby amends Title XV Land Use: Chapter 154 Zoning Code; Article XI Rural District: by amending Section 154.406 Accessory Structures, Rural Districts;

154.406 ACCESSORY STRUCTURES, RURAL DISTRICTS.

B. Structure Height, Rural Districts. No accessory building shall exceed twenty-two (22) feet in height or the height of the principal structure, with the exception of agricultural buildings, as defined in §154.213. Building projections or features on accessory structures that are not agricultural buildings as defined in §154.213, such as chimneys, cupolas, and similar decorations that do not exceed twenty-five (25) feet in height are permitted in rural districts.

~~F. — Openings and Doors. Garage doors and other openings shall not exceed fourteen (14) feet in height for all accessory structures, with the exception of buildings that are intended for a farming or other agricultural use in the judgment of the City.~~

SECTION 2. The City Council of the City of Lake Elmo hereby amends Title XV Land Use: Chapter 154 Zoning Code; Article XVII Open Space Planned Unit Development: by amending Section 154.658 Openspace Development Standards, Building Standards;

C. Building Standards

~~2. Accessory structures within open space planned unit developments shall not exceed 22 feet in height.~~

SECTION 3. The City Council of the City of Lake Elmo hereby amends the Code of Ordinances Title I: Chapter 11 General Code Provisions; by amending 11.01 Definitions;

11.01 DEFINITIONS.

~~**BUILDING HEIGHT.** — The vertical distance from the average of the highest and lowest point of grade for that portion of the lot covered by building to the highest point of the roof for flat roofs; to the roof deck line of mansard roofs; and to the mean height between eaves and highest ridge for gable, hip, and gambrel roofs.~~

BUILDING HEIGHT - Means the vertical distance between the average of the ground level elevation(s) to the top of a flat roof, the deck line of a mansard roof, or the midpoint on a pitched roof which is between the highest point (peak of building) and lowest point (bottom of the truss at the top plate of the wall) on the roof.

SECTION 4. Effective Date. This ordinance shall become effective immediately upon adoption and publication in the official newspaper of the City of Lake Elmo.


SECTION 5. Adoption Date. This Ordinance 08-³⁰~~29~~ was adopted on this 5th day of Nov., 2019, by a vote of 5 Ayes and 0 Nays.

LAKE ELMO CITY COUNCIL



Mike Pearson, Mayor

ATTEST:



Julie Johnson, City Clerk

This Ordinance 08-236 was published on the ____ day of _____, 2019.